

TOSHIBA PHOTOCOUPLER GaAs IRED & PHOTO-THYRISTOR

TLP541G, TLP542G

PROGRAMMABLE CONTROLLERS

AC-OUTPUT MODULE


SOLID STATE RELAY

The TOSHIBA TLP541G consists of a photo-thyristor optically coupled to a gallium arsenide infrared emitting diode in a six lead plastic DIP package.


The TOSHIBA TLP542G consists of a photo-thyristor optically coupled to a gallium arsenide infrared emitting diode in a seven lead plastic DIP package.

- Peak Off-State Voltage : 400V (MIN.)
- Trigger LED Current : 7mA (MAX.)
- On-State Current : 150mA (MAX.)
- Isolation Voltage : 2500V_{rms} (MIN.)
- UL Recognized : UL1577, File No. E67349


PIN CONFIGURATION (TOP VIEW)



Unit in mm



Weight : 0.4g



Weight : 0.53g

961001EAA2

- TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

MAXIMUM RATINGS (Ta = 25°C)

CHARACTERISTIC		SYMBOL	RATING	UNIT
LED	Forward Current	I _F	70	mA
	Forward Current Derating (Ta ≥ 25°C)	ΔI _F / °C	-0.7	mA / °C
	Peak Forward Current (100μs pulse, 100pps)	I _{FP}	1	A
	Reverse Voltage	V _R	5	V
	Junction Temperature	T _j	125	°C
DETECTOR	Peak Forward Voltage (R _{GK} = 27kΩ)	V _{DRM}	400	V
	Peak Reverse Voltage (R _{GK} = 27kΩ)	V _{RDM}	400	V
	On-State Current	I _T (RMS)	150	mA
	On-State Current Derating (Ta ≥ 25°C)	ΔI _T / °C	-2.0	mA / °C
	Peak One Cycle Surge Current	I _{TSM}	2	A
	Peak Reverse Gate Voltage	V _{GM}	-5	V
	Junction Temperature	T _j	100	°C
Storage Temperature Range		T _{stg}	-55~125	°C
Operating Temperature Range		T _{opr}	-30~100	°C
Lead Soldering Temperature (10s)		T _{sol}	260	°C
Isolation Voltage (AC, 1 min., R.H. ≤ 60%) (Note)		BV _S	2500	V _{rms}

(Note) Device considered a two terminal device : LED side pins shorted together and DETECTOR side pins shorted together.

RECOMMENDED OPERATING CONDITIONS

CHARACTERISTIC	SYMBOL	MIN.	TYP.	MAX.	UNIT
Supply Voltage	V _{AC}	—	—	120	V _{ac}
Forward Current	I _F	10	16	25	mA
Operating Temperature	T _{opr}	-30	—	85	°C
Gate to Cathode Resistance	R _{GK}	—	27	33	kΩ
Gate to Cathode Capacity	C _{GK}	—	0.01	0.1	μF

INDIVIDUAL ELECTRICAL CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC		SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT	
LED	Forward Voltage	V_F	$I_F = 10\text{mA}$	1.0	1.15	1.3	V	
	Reverse Current	I_R	$V_R = 5\text{V}$	—	—	10	μA	
	Capacitance	C_T	$V = 0, f = 1\text{MHz}$	—	30	—	pF	
DETECTOR	Off-State Current	I_{DRM}	$V_{AK} = 400\text{V}$ $R_{GK} = 27\text{k}\Omega$	Ta = 25°C	—	10	5000	nA
				Ta = 100°C	—	1	100	μA
	Reverse Current	I_{RRM}	$V_{KA} = 400\text{V}$ $R_{GK} = 27\text{k}\Omega$	Ta = 25°C	—	10	5000	nA
				Ta = 100°C	—	1	100	μA
	On-State Voltage	V_{TM}	$I_{TM} = 100\text{mA}$	—	0.9	1.3	V	
	Holding Current	I_H	$R_{GK} = 27\text{k}\Omega$	—	0.2	1	mA	
	Off-State dv/dt	dv/dt	$V_{AK} = 280\text{V}, R_{GK} = 27\text{k}\Omega$	5	10	—	V/ μs	
Capacitance	C_j	V = 0, f = 1MHz Anode to Gate	—	20	—	pF		
		Gate to Cathode	—	350	—			

COUPLED CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Trigger LED Current	I_{FT}	$V_{AK} = 6\text{V}, R_{GK} = 27\text{k}\Omega$	1	4	7	mA
Turn-on Time	t_{on}	$I_F = 50\text{mA}, R_{GK} = 27\text{k}\Omega$	—	10	—	μs
Capacitance (Input to Output)	C_S	$V_S = 0, f = 1\text{MHz}$	—	0.8	—	pF
Isolation Resistance	R_S	$V_S = 500\text{V}, \text{R.H.} \leq 60\%$	—	10^{11}	—	Ω
Isolation Voltage	BV_S	AC, 1 minute	2500	—	—	V_{rms}

