

FAIRCHILD

A Schlumberger Company

2N3253

T-35-19

NPN Switching Type

ABSOLUTE MAXIMUM RATINGS (Note 1)**Temperatures**

Storage Temperature	-65° C to 200° C
Operating Junction Temperature	200° C

PACKAGE

2N3253 TO-39

Power Dissipation (Notes 2 & 3)

Total Dissipation at	
25° C Ambient Temperature	0.8 W
25° C Case Temperature	3.0 W

Voltages & Currents

V _{CEO} Collector to Emitter Voltage (Note 4)	40 V
V _{CBO} Collector to Base Voltage	75 V
V _{EBO} Emitter to Base Voltage	5.0 V
I _C Collector Current	1.0 A

ELECTRICAL CHARACTERISTICS (25° C Ambient Temperature unless otherwise noted) (Note 6)

SYMBOL	CHARACTERISTIC	MIN	MAX	UNITS	TEST CONDITIONS
BV _{CBO}	Collector to Base Breakdown Voltage	75		V	I _C = 10 μA, I _E = 0
BV _{EBO}	Emitter to Base Breakdown Voltage	5.0		V	I _E = 10 μA, I _C = 0
I _{EBO}	Emitter Cutoff Current		50	nA	V _{EB} = 4.0 V, I _C = 0
I _{CBO}	Collector Reverse Current (100° C)		500 75	nA μA	V _{CB} = 60 V, I _E = 0 V _{CB} = 60 V, I _E = 0
I _{CEX}	Collector Reverse Current		500	nA	V _{CE} = 60 V, V _{EB} = 4.0 V
I _{BL}	Base Current		500	nA	V _{CE} = 60 V, V _{OB} = 4.0 V
h _{FE}	DC Pulse Current Gain (Note 5)	25 25 20	75		I _C = 150 mA, V _{CE} = 1.0 V I _C = 375 mA, V _{CE} = 1.0 V I _C = 750 mA, V _{CE} = 5.0 V
V _{CEO(sus)}	Collector to Emitter Sustaining Voltage (Notes 4 & 5)	40		V	I _C = 10 mA, I _B = 0
V _{CE(sat)}	Collector to Emitter Saturation Voltage (Pulsed) (Note 5)		0.35 0.6 1.2	V V V	I _C = 150 mA, I _B = 15 mA I _C = 500 mA, I _B = 50 mA I _C = 1.0 A, I _B = 100 mA
V _{BE(sat)}	Base to Emitter Saturation Voltage (Pulsed) (Note 5)	0.7	1.0 1.3 1.8	V V V	I _C = 150 mA, I _B = 15 mA I _C = 500 mA, I _B = 50 mA I _C = 1.0 A, I _B = 100 mA

NOTES:

- These ratings are limiting values above which the serviceability of any individual semiconductor device may be impaired.
- These are steady state limits. The factory should be consulted on applications involving pulsed or low duty cycle operations.
- These ratings give a maximum junction temperature of 150° C and (TO-92) junction-to-case thermal resistance of 125° C/W (derating factor of 8.0 mW/° C); junction-to-ambient thermal resistance of 200° C/W (derating factor of 5.0 mW/° C); (TO-238) junction-to-ambient thermal resistance of 357° C/W (derating factor of 2.8 mW/° C).
- Rating refers to a high current point where collector to emitter voltage is lowest.
- Pulse conditions: length = 300 μs; duty cycle ≤ 1%.
- For product family characteristic curves, refer to Curve Set T139.

ELECTRICAL CHARACTERISTICS (25° C Ambient Temperature unless otherwise noted) (Note 6)

SYMBOL	CHARACTERISTIC	MIN	MAX	UNITS	TEST CONDITIONS
C_{ob}	Output Capacitance		12	pF	$V_{CB} = 20 \text{ V}$, $I_E = 0$
C_{ib}	Input Capacitance		80	pF	$V_{EB} = 0.5 \text{ V}$, $I_C = 0$
h_{fe}	High Frequency Current Gain	1.75			$I_C = 50 \text{ mA}$, $V_{CE} = 10 \text{ V}$, $f = 100 \text{ MHz}$
t_d	Turn On Delay Time (test circuit no. 3164)		15	ns	$I_C = 500 \text{ mA}$, $I_{B1} = 50 \text{ mA}$
t_r	Rise Time (test circuit no. 3164)		35	ns	$I_C = 500 \text{ mA}$, $I_{B1} = 50 \text{ mA}$
t_s	Storage Time (test circuit no. 3165)		40	ns	$I_C = 500 \text{ mA}$, $I_{B1} = I_{B2} = 50 \text{ mA}$
t_f	Fall Time (test circuit no. 3165)		30	ns	$I_C = 500 \text{ mA}$, $I_{B1} = I_{B2} = 50 \text{ mA}$
Q_T	Total Control Charge (test circuit no. 3163)		5.0	ncoul	$I_C = 500 \text{ mA}$, $I_B = 50 \text{ mA}$



2N3700/2N3701 T-29-23
 NPN Small Signal General Purpose Amplifiers

- $V_{CE0} \dots 80 \text{ V (Min) @ } 30 \text{ mA}$
- $V_{CE(sat)} \dots 0.5 \text{ V (Max) @ } 500 \text{ mA}$

PACKAGE	
2N3700	TO-18
2N3701	TO-18

ABSOLUTE MAXIMUM RATINGS (Note 1)

Temperatures

Storage Temperature	-65° C to 200° C
Operating Junction Temperature	200° C

Power Dissipation (Notes 2 & 3)

Total Dissipation at 25° C Ambient Temperature	0.5 W
100° C Case Temperature	1.0 W
25° C Case Temperature	1.8 W

Voltages & Currents

V_{CE0} Collector to Emitter Voltage (Note 4)	80 V
V_{CBO} Collector to Base Voltage	140 V
V_{EBO} Emitter to Base Voltage	7.0 V
I_C Collector Current	1.0 A

ELECTRICAL CHARACTERISTICS (25° C Ambient Temperature unless otherwise noted) (Note 6)

SYMBOL	CHARACTERISTIC	3700		3701		UNITS	TEST CONDITIONS
		MIN	MAX	MIN	MAX		
BV_{CBO}	Collector to Base Breakdown Voltage	140		140		V	$I_C = 100 \mu\text{A}, I_E = 0$
BV_{EBO}	Emitter to Base Breakdown Voltage	7.0		7.0		V	$I_E = 100 \mu\text{A}, I_C = 0$
I_{EBO}	Emitter Cutoff Current		10		10	nA	$V_{EB} = 5.0 \text{ V}, I_C = 0$
I_{CBO}	Collector Cutoff Current		10		10	nA	$V_{CB} = 90 \text{ V}, I_E = 0$
			10		10	μA	$V_{CB} = 90 \text{ V}, I_E = 0, T_A = 150^\circ \text{ C}$
h_{FE}	DC Pulse Current Gain (Note 5)	100	300	40	120		$I_C = 150 \text{ mA}, V_{CE} = 10 \text{ V}$
		90		40	120		$I_C = 10 \text{ mA}, V_{CE} = 10 \text{ V}$
		50		30	100		$I_C = 0.1 \text{ mA}, V_{CE} = 10 \text{ V}$
		50		30	100		$I_C = 500 \text{ mA}, V_{CE} = 10 \text{ V}$
		15		15			$I_C = 1.0 \text{ mA}, V_{CE} = 10 \text{ V}$
		40					$I_C = 150 \text{ mA}, V_{CE} = 10 \text{ V}, T_A = -55^\circ \text{ C}$

NOTES:

1. These ratings are limiting values above which the serviceability of any individual semiconductor device may be impaired.
2. These are steady state limits. The factory should be consulted on applications involving pulsed or low duty cycle operations.
3. These ratings give a maximum junction temperature of 200° C and junction-to-case thermal resistance of 97° C/W (derating factor of 10.3 mW/° C); junction-to-ambient thermal resistance of 350° C/W (derating factor of 2.85 mW/° C).
4. Rating refers to a high current point where collector to emitter voltage is lowest.
5. Pulse conditions: length = 300 μs ; duty cycle $\leq 1\%$.
6. For product family characteristic curves, refer to Curve Set T149.

3469674 FAIRCHILD SEMICONDUCTOR

84D 27555 D

2N3700/2N3701

T-29-23

ELECTRICAL CHARACTERISTICS (25° C Ambient Temperature unless otherwise noted) (Note 6)

SYMBOL	CHARACTERISTIC	3700		3701		UNITS	TEST CONDITIONS
		MIN	MAX	MIN	MAX		
$V_{CE(sus)}$	Collector to Emitter Sustaining Voltage (Notes 4 & 5)	80		80		V	$I_C = 30 \text{ mA}, I_B = 0$
$V_{CE(sat)}$	Pulsed Collector to Emitter Saturation Voltage (Note 5)		0.2 0.5		0.2 0.5	V V	$I_C = 150 \text{ mA}, I_B = 15 \text{ mA}$ $I_C = 500 \text{ mA}, I_B = 50 \text{ mA}$
$V_{BE(sat)}$	Base to Emitter Saturation Voltage (Pulsed)		1.1		1.1	V	$I_C = 150 \text{ mA}, I_B = 15 \text{ mA}$
C_{ob}	Output Capacitance		12		12	pF	$V_{CB} = 10 \text{ V}, I_E = 0, f = 1.0 \text{ MHz}$
C_{ib}	Input Capacitance		60		60	pF	$V_{EB} = 0.5 \text{ V}, I_C = 0, f = 1.0 \text{ MHz}$
h_{fe}	High Frequency Current Gain	5.0	10	4.0	10		$I_C = 50 \text{ mA}, V_{CE} = 10 \text{ V}, f = 20 \text{ MHz}$
h_{ie}	Small Signal Current Gain	80	400	30	200		$I_C = 1.0 \text{ mA}, V_{CE} = 5.0 \text{ V}, f = 1.0 \text{ kHz}$
$r_b'C_c$	Collector to Base Time Constant	25	400	25	400	ps	$I_C = 10 \text{ mA}, V_{CB} = 10 \text{ V}, f = 4.0 \text{ MHz}$
NF	Noise Figure		4.0			dB	$I_C = 100 \mu\text{A}, V_{CE} = 10 \text{ V}, f = 1.0 \text{ kHz}, R_G = 1.0 \text{ k}\Omega$

FAIRCHILD

A Schlumberger Company

2N3724/2N3725
2N4013/2N4014

T-35-15

NPN Small Signal High Current High
Speed Switches

- $V_{CE0} \dots 30 \text{ V (Min)}$ (2N3724, 2N4013), 50 V (Min) (2N3725, 2N4014)
- $V_{CE(sat)} \dots 0.65 \text{ V (Max)}$ @ 800 mA, 0.75 V (Max) @ 1.0 A (2N3724, 2N4013)
- $f_{FE} \dots 60\text{-}150$ @ 1.0 A (2N3724, 2N4013)
- $t_{on} \dots 35 \text{ ns (Max)}$, $t_{off} \dots 60 \text{ ns (Max)}$ @ 500 mA

PACKAGE

2N3724	TO-5
2N3725	TO-5
2N4013	TO-18
2N4014	TO-18

ABSOLUTE MAXIMUM RATINGS (Note 1)**Temperatures**

Storage Temperature	-65° C to 200° C
Operating Junction Temperature	200° C

Power Dissipation (Notes 2 & 3)

Total Dissipation at	4013/4	3724/5
25° C Ambient Temperature	0.36 W	0.8 W
25° C Case Temperature	1.2 W	3.5 W

Voltages & Currents

	3724/4013	3725/4014
V_{CE0} Collector to Emitter Voltage (Note 4)	30 V	50 V
V_{CBO} Collector to Base Voltage	50 V	80 V
V_{CES} Collector to Emitter Voltage	50 V	80 V
V_{EBO} Emitter to Base Voltage	6.0 V	6.0 V
I_C Collector Current (Note 5)	1.0 A	1.0 A
I_C DC Collector Current	500 mA	500 mA

ELECTRICAL CHARACTERISTICS (25° C Ambient Temperature unless otherwise noted) (Note 6)

SYMBOL	CHARACTERISTIC	3724/4013		3725/4014		UNITS	TEST CONDITIONS
		MIN	MAX	MIN	MAX		
BV_{CES}	Collector to Emitter Breakdown Voltage	50		80		V	$I_C = 10 \mu\text{A}$, $V_{BE} = 0$
BV_{CBO}	Collector to Base Breakdown Voltage	50		50		V	$I_C = 10 \mu\text{A}$, $I_E = 0$
BV_{EBO}	Emitter to Base Breakdown Voltage	6.0		6.0		V	$I_E = 10 \mu\text{A}$, $I_C = 0$

NOTES:

1. These ratings are limiting values above which the serviceability of any individual semiconductor device may be impaired.
2. These are steady state limits. The factory should be consulted on applications involving pulsed or low duty cycle operations.
3. These ratings give a maximum junction temperature of 200° C and junction-to-case thermal resistance of 50° C/W (derating factor of 20 mW/° C) for 2N3724 and 2N3725; and 146° C/W (derating factor of 6.85 mW/° C) for the 2N4013 and 2N4014; junction-to-ambient thermal resistance of 219° C/W (derating factor of 4.56 mW/° C) for the 2N3724, 2N3725, and 485° C/W (derating factor of 2.06 mW/° C) for the 2N4013 and 2N4014.
4. Rating refers to a high current point where collector to emitter voltage is lowest.
5. Pulse conditions: length = 300 μs ; duty cycle = 1%.
6. For product family characteristic curves, refer to Curve Set T162 for 2N3724/5 and T139 for 2N4013/4

3469674 FAIRCHILD SEMICONDUCTOR

84D 27557 D

2N3724/2N3725
2N4013/2N4014

T-35-15

ELECTRICAL CHARACTERISTICS (25° C Ambient Temperature unless otherwise noted) (Note 6)

SYMBOL	CHARACTERISTIC	3724/4013		3725/4014		UNITS	TEST CONDITIONS
		MIN	MAX	MIN	MAX		
I_{CBO}	Collector Cutoff Current		1.7			μA	$V_{CB} = 40 V, I_E = 0$
					1.7	μA	$V_{CB} = 60 V, I_E = 0$
			120		120	μA	$V_{CB} = 40 V, I_E = 0, T_A = 100^\circ C$ $V_{CB} = 60 V, I_E = 0, T_A = 100^\circ C$
I_{CES}	Collector Reverse Current		10		10	μA	$V_{CE} = 50 V, I_E = 0$ $V_{CE} = 80 V, I_E = 0$
h_{FE}	DC Pulse Current Gain (Note 5)	60	150	60	150		$I_C = 100 mA, V_{CE} = 1.0 V$
		35		35			$I_C = 500 mA, V_{CE} = 1.0 V$
		40		40			$I_C = 300 mA, V_{CE} = 1.0 V$
		30		25			$I_C = 1.0 A, V_{CE} = 5.0 V$
		30		30			$I_C = 10 mA, V_{CE} = 1.0 V$
		25		20			$I_C = 800 mA, V_{CE} = 2.0 V$
		30		30			$I_C = 100 mA, V_{CE} = 1.0 V,$ $T_A = -55^\circ C$
		20		20			$I_C = 500 mA, V_{CE} = 1.0 V,$ $T_A = -55^\circ C$
$V_{CE(sus)}$	Collector to Emitter Sustaining Voltage (Notes 4 & 5)	30		50		V	$I_C = 10 mA, I_B = 0$
$V_{CE(sat)}$	Collector to Emitter Saturation Voltage (Note 5)		0.25		0.25	V	$I_C = 10 mA, I_B = 1.0 mA$
			0.2		0.26	V	$I_C = 100 mA, I_B = 10 mA$
			0.32		0.4	V	$I_C = 300 mA, I_B = 30 mA$
			0.42		0.52	V	$I_C = 500 mA, I_B = 50 mA$
			0.65		0.8	V	$I_C = 800 mA, I_B = 80 mA$
			0.75		0.95	V	$I_C = 1.0 A, I_B = 100 mA$
$V_{BE(sat)}$	Base to Emitter Saturation Voltage (Note 5)		0.76		0.76	V	$I_C = 10 mA, I_B = 1.0 mA$
			0.86		0.86	V	$I_C = 100 mA, I_B = 10 mA$
			1.1		1.1	V	$I_C = 300 mA, I_B = 30 mA$
			1.5		1.5	V	$I_C = 800 mA, I_B = 80 mA$
			1.7		1.7	V	$I_C = 1.0 A, I_B = 100 mA$
		0.8	1.1	0.8	1.1	V	$I_C = 500 mA, I_B = 50 mA$
C_{ob}	Output Capacitance		12		10	pF	$V_{CB} = 10 V, I_E = 0$
C_{ib}	Input Capacitance		55		55	pF	$V_{BE} = 0.5 V, I_C = 0$
h_{fe}	High Frequency Current Gain	3.0		3.0			$I_C = 50 mA, V_{CE} = 10 V,$ $f = 100 MHz$
t_{on}	Turn On Time (test circuit no. 265)		35		35	ns	$I_C = 500 mA, I_{B1} = 50 mA$
t_{off}	Turn Off Time (test circuit no. 265)		60		60	ns	$I_C = 500 mA, I_{B1} = 50 mA,$ $I_{B2} = -50 mA$

3469674 FAIRCHILD SEMICONDUCTOR

84D 27558 D

FAIRCHILD

A Schlumberger Company

2N3903/FTSO3903 7-35-15
2N3904/FTSO3904

NPN Small Signal General Purpose Amplifiers & Switches

- V_{CE0} ... 40 V (Min)
- h_{FE} ... 100-300 @ 10 mA (2N/FTSO3904)
- NF ... 5.0 dB (Max) Wide Band (2N/FTSO3904)
- Complements ... 2N3905, 2N3906

PACKAGE

2N3903	TO-92
2N3904	TO-92
FTSO3903	TO-236AA/AB
FTSO3904	TO-236AA/AB

ABSOLUTE MAXIMUM RATINGS (Note 1)

Temperatures

Storage Temperature	-55° C to 150° C
Operating Junction Temperature	150° C

Power Dissipation (Notes 2 & 3)

Total Dissipation at	2N	FTSO
25° C Ambient Temperature	0.625 W	0.350 W*
70° C Ambient Temperature	0.400 W	
25° C Case Temperature	1.0 W	

Voltages & Currents

V_{CE0} Collector to Emitter Voltage	40 V
(Note 4)	
V_{CBO} Collector to Base Voltage	60 V
V_{EBO} Emitter to Base Voltage	6.0 V
I_C Collector Current	200 mA

ELECTRICAL CHARACTERISTICS (25° C Ambient Temperature unless otherwise noted) (Note 5)

SYMBOL	CHARACTERISTIC	3903		3904		UNITS	TEST CONDITIONS
		MIN	MAX	MIN	MAX		
BV_{CE0}	Collector to Emitter Breakdown Voltage (Note 4)	40		40		V	$I_C = 1.0$ mA, $I_B = 0$
BV_{CBO}	Collector to Base Breakdown Voltage	60		60		V	$I_C = 10$ μ A, $I_E = 0$
BV_{EBO}	Emitter to Base Breakdown Voltage	6.0		6.0		V	$I_E = 10$ μ A, $I_C = 0$
I_{CEX}	Collector Cutoff Current		50		50	nA	$V_{CE} = 30$ V, $V_{EB} = 3.0$ V
I_{BL}	Base Cutoff Current		50		50	nA	$V_{CE} = 30$ V, $V_{EB} = 3.0$ V
h_{FE}	DC Current Gain (Note 4)	20 35 50 30 15	150	40 70 100 60 30	300		$I_C = 0.1$ mA, $V_{CE} = 1.0$ V $I_C = 1.0$ mA, $V_{CE} = 1.0$ V $I_C = 10$ mA, $V_{CE} = 1.0$ V $I_C = 50$ mA, $V_{CE} = 1.0$ V $I_C = 100$ mA, $V_{CE} = 1.0$ V

NOTES:

1. These ratings are limiting values above which the serviceability of any individual semiconductor device may be impaired.
 2. These are steady state limits. The factory should be consulted on applications involving pulsed or low duty cycle operations.
 3. These ratings give a maximum junction temperature of 150° C and (TO-92) junction-to-case thermal resistance of 125° C/W (derating factor of 8.0 mW/° C); junction-to-ambient thermal resistance of 200° C/W (derating factor of 5.0 mW/° C); (TO-236) junction-to-ambient thermal resistance of 357° C/W (derating factor of 2.8 mW/° C).
 4. Pulse conditions: length = 300 μ s; duty cycle = 2%.
 5. For product family characteristic curves, refer to Curve Set T144.
- * Package mounted on 99.5% alumina 8 mm x 8 mm x 0.6 mm.

2N3903/FTSO3903
2N3904/FTSO3904

T-35-15

ELECTRICAL CHARACTERISTICS (25° C Ambient Temperature unless otherwise noted) (Note 5)

SYMBOL	CHARACTERISTIC	3903		3904		UNITS	TEST CONDITIONS
		MIN	MAX	MIN	MAX		
$V_{CE(sat)}$	Collector to Emitter Saturation Voltage (Note 4)		0.2 0.3		0.2 0.3	V V	$I_C = 10 \text{ mA}$, $I_B = 1.0 \text{ mA}$ $I_C = 50 \text{ mA}$, $I_B = 5.0 \text{ mA}$
$V_{BE(sat)}$	Base to Emitter Saturation Voltage (Note 4)	0.65	0.85 0.95	0.65	0.85 0.95	V V	$I_C = 10 \text{ mA}$, $I_B = 1.0 \text{ mA}$ $I_C = 50 \text{ mA}$, $I_B = 5.0 \text{ mA}$
C_{ob}	Output Capacitance		4.0		4.0	pF	$V_{CB} = 5.0 \text{ V}$, $I_E = 0$, $f = 100 \text{ kHz}$
C_{ib}	Input Capacitance		8.0		8.0	pF	$V_{BE} = 0.5 \text{ V}$, $I_C = 0$, $f = 100 \text{ kHz}$
h_{fe}	Small Signal Current Gain	50	200	100	400		$I_C = 1.0 \text{ mA}$, $V_{CE} = 10 \text{ V}$, $f = 1.0 \text{ kHz}$
h_{ie}	Input Impedance	1.0	8.0	1.0	10	k Ω	$I_C = 1.0 \text{ mA}$, $V_{CE} = 10 \text{ V}$, $f = 1.0 \text{ kHz}$
h_{oe}	Output Admittance	1.0	40	1.0	40	μmho	$I_C = 1.0 \text{ mA}$, $V_{CE} = 10 \text{ V}$, $f = 1.0 \text{ kHz}$
h_{re}	Voltage Feedback Ratio	0.1	5.0	0.5	8.0	$\times 10^{-4}$	$I_C = 1.0 \text{ mA}$, $V_{CE} = 10 \text{ V}$, $f = 1.0 \text{ kHz}$
f_T	Current Gain Bandwidth Product	250		300		MHz	$I_C = 10 \text{ mA}$, $V_{CE} = 20 \text{ V}$, $f = 100 \text{ MHz}$
t_d	Turn On Delay Time (test circuit no. 526)		35		35	ns	$I_C = 10 \text{ mA}$, $V_{CC} = 3.0 \text{ V}$, $I_{B1} = 10 \text{ mA}$, $V_{BE(OFF)} = 0.5 \text{ V}$
t_r	Rise Time (test circuit no. 526)		35		35	ns	$I_C = 10 \text{ mA}$, $V_{CC} = 3.0 \text{ V}$, $I_{B1} = 10 \text{ mA}$, $V_{BE(OFF)} = 0.5 \text{ V}$
t_s	Storage Time (test circuit no. 527)		175		200	ns	$I_C = 10 \text{ mA}$, $V_{CC} = 3.0 \text{ V}$, $I_{B1} = I_{B2} = 1.0 \text{ mA}$
t_f	Fall Time (test circuit no. 527)		50		50	ns	$I_C = 10 \text{ mA}$, $V_{CC} = 3.0 \text{ V}$, $I_{B1} = I_{B2} = 1.0 \text{ mA}$
NF	Noise Figure		6.0		5.0	dB	$I_C = 100 \mu\text{A}$, $V_{CE} = 5.0 \text{ V}$, $f = 10 \text{ Hz}$ to 15.7 kHz , $R_G = 1.0 \text{ k}\Omega$

3469674 FAIRCHILD SEMICONDUCTOR

84D 27560 D ■



2N3905/FTSO3905 T-37-15
2N3906/FTSO3906
 PNP Small Signal General Purpose
 Amplifiers & Switches

- V_{CE0} ... -40 V (Min)
- h_{FE} ... 100-300 @ 10 mA (2N3906)
- NF ... 4.0 dB (Max) Wide Band (2N3906)
- Complements ... 2N3903, 2N3904

PACKAGE	
2N3905	TO-92
2N3906	TO-92
FTSO3905	TO-236AA/AB
FTSO3906	TO-236AA/AB

ABSOLUTE MAXIMUM RATINGS (Note 1)

Temperatures

Storage Temperature -55° C to 150° C
 Operating Junction Temperature 150° C

Power Dissipation (Notes 2 & 3)

Total Dissipation at	2N	FTSO
25° C Ambient Temperature	0.625 W	0.350 W*
70° C Ambient Temperature	0.400 W	
25° C Case Temperature	1.0 W	

Voltages & Currents

V_{CE0} Collector to Emitter Voltage (Note 4)	-40 V
V_{CBO} Collector to Base Voltage	-40 V
V_{EBO} Emitter to Base Voltage	-5.0 V
I_C Collector Current	200 mA

ELECTRICAL CHARACTERISTICS (25° C Ambient Temperature unless otherwise noted) (Note 6)

SYMBOL	CHARACTERISTIC	3905		3906		UNITS	TEST CONDITIONS
		MIN	MAX	MIN	MAX		
BV_{CE0}	Collector to Emitter Breakdown Voltage (Note 5)	-40		-40		V	$I_C = 1.0$ mA, $I_B = 0$
BV_{CBO}	Collector to Base Breakdown Voltage	-40		-40		V	$I_C = 10$ μ A, $I_E = 0$
BV_{EBO}	Emitter to Base Breakdown Voltage	-5.0		-5.0		V	$I_E = 10$ μ A, $I_C = 0$
I_{CEX}	Collector Cutoff Current		50		50	nA	$V_{CE} = -30$ V, $V_{EB} = -3.0$ V
I_{BL}	Base Cutoff Current		50		50	nA	$V_{CE} = -30$ V, $V_{EB} = -3.0$ V
h_{FE}	DC Pulse Current Gain (Note 5)	30 40 50 30 15	150	60 80 100 60 30	300		$I_C = 0.1$ mA, $V_{CE} = -1.0$ V $I_C = 1.0$ mA, $V_{CE} = -1.0$ V $I_C = 10$ mA, $V_{CE} = -1.0$ V $I_C = 50$ mA, $V_{CE} = -1.0$ V $I_C = 100$ mA, $V_{CE} = -1.0$ V

NOTES:

1. These ratings are limiting values above which the serviceability of any individual semiconductor device may be impaired.
 2. These are steady state limits. The factory should be consulted on applications involving pulsed or low duty cycle operations.
 3. These ratings give a maximum junction temperature of 150° C and (TO-92) junction-to-case thermal resistance of 125° C/W (derating factor of 8.0 mW/° C); junction-to-ambient thermal resistance of 200° C/W (derating factor of 5.0 mW/° C); (TO-236) junction-to-ambient thermal resistance of 357° C/W (derating factor of 2.8 mW/° C).
 4. Rating refers to a high current point where collector to emitter voltage is lowest.
 5. Pulse conditions: length = 300 μ s; duty cycle \leq 2%.
 6. For product family characteristic curves, refer to Curve Set T215.
- * Package mounted on 99.5% alumina 8 mm x 8 mm x 0.6 mm.

2N3905/FTSO3905
2N3906/FTSO3906 T-37-15

ELECTRICAL CHARACTERISTICS (25° C Ambient Temperature unless otherwise noted) (Note 6)

SYMBOL	CHARACTERISTIC	3905		3906		UNITS	TEST CONDITIONS
		MIN	MAX	MIN	MAX		
V _{CE(sat)}	Collector to Emitter Saturation Voltage (Note 5)		-0.25		-0.25	V	I _C = 10 mA, I _B = 1.0 mA
			-0.4		-0.4	V	I _C = 50 mA, I _B = 5.0 mA
V _{BE(sat)}	Base to Emitter Saturation Voltage (Note 5)	-0.65	-0.85	-0.65	-0.85	V	I _C = 10 mA, I _B = 1.0 mA
			-0.95		-0.95	V	I _C = 50 mA, I _B = 5.0 mA
C _{ob}	Output Capacitance		4.5		4.5	pF	V _{CB} = -5.0 V, I _E = 0, f = 100 kHz
C _{ib}	Input Capacitance		10		10	pF	V _{EB} = -0.5 V, I _C = 0, f = 100 kHz
h _{ie}	Small Signal Current Gain	50	200	100	400		I _C = 1.0 mA, V _{CE} = -10 V, f = 1.0 kHz
h _{ie}	Input Impedance	0.5	8.0	2.0	10	kΩ	I _C = 1.0 mA, V _{CE} = -10 V, f = 1.0 kHz
h _{oe}	Output Admittance	1.0	40	3.0	60	μmho	I _C = 1.0 mA, V _{CE} = -10 V, f = 1.0 kHz
h _{re}	Voltage Feedback Ratio	0.1	5.0	0.1	10	x10 ⁻⁴	I _C = 1.0 mA, V _{CE} = -10 V, f = 1.0 kHz
f _T	Current Gain Bandwidth Product	200		250		MHz	I _C = 10 mA, V _{CE} = -20 V, f = 100 MHz
t _d	Turn On Delay Time (test circuit no. 333)		35		35	ns	I _C ≅ 10 mA, I _{B1} ≅ 1.0 mA, V _{CC} = -3.0 V
t _r	Rise Time (test circuit no. 333)		35		35	ns	I _C ≅ 10 mA, I _{B1} ≅ 1.0 mA, V _{CC} = -3.0 V
t _s	Storage Time (test circuit no. 239)		200		225	ns	I _C ≅ 10 mA, I _{B1} ≅ 1.0 mA, I _{B2} ≅ -1.0 mA, V _{CC} = -3.0 V
t _f	Fall Time (test circuit no. 239)		60		75	ns	I _C ≅ 10 mA, I _{B1} ≅ 1.0 mA, I _{B2} ≅ -1.0 mA, V _{CC} = -3.0 V
NF	Wide Band Noise Figure		5.0		4.0	dB	I _C = 100 μA, V _{CE} = -5.0 V, R _S = 1.0 kΩ, f = 10 Hz to 15.7 kHz